

IN THE SPECIFICATION:

Please amend paragraph 0018, as follows:

[0018] As shown in the embodiment shown in FIGS. 4A, 4B and 5A, the communication port 222 is installed in a slide groove 201 of the battery unit 210 to slide and protrude. ~~Thus, be~~By sliding the communication port 222, the communication port 222 is inserted into a USB port 301 of a computer 300 or a PDA. Thus, when the memory unit 220 is connected to another device 300, such as a PDA, the communication port 222 protrudes and then is inserted into a ~~the~~ USB port 301 of the another device 300 to allow information to be exchanged between the memory unit 220 and the device 300.

Please amend paragraph 0023, as follows:

[0023] However, when the battery 200 is connected to a different kind of device 300, such as a different kind of portable phone, a ~~notebooks~~notebook, or a PDA shown in FIG. 5A or 5B, the communication port 222 built into the battery 200 is inserted into the USB port 301 of another device 300. Then, the memory unit 220 is connected to the device 300 using the communication port 222 and the USB port 301 to interchange information with the device 300. Thus, information stored in the memory unit 220 may be transmitted to the device 300, and information stored in the device 300 may be transmitted to the memory unit 220. If the device 300 is supplied with power from the battery unit 220 of the battery 200, as shown in FIG. 6, the power output port 211 of the battery 200 is connected to the power input port 302 of the device 300 using the connection cable 400. Then, the device 300 is supplied with power from the battery 200 of the portable phone to operate.